


三通阀 (3-Way Valves)

- 可对应各种连接方式。
- 接流体部全部都是氟化乙烯树脂(PFA/PTFE)，抗腐蚀。
- 超低粉尘清理(表面粗糙度加工、精密洗净、平面构造)。
- MRM独自的安全构造(高压对策及热循环对策)。



型号表示方法 (How to order)

SAP3D - □ - □ □ - □ □ - □ □ - □ - □

↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

型号选定例 (Model Number Selection example)

SAP3D-15-SB-29-10-Y

: 1/2" (× 3/8"), Pillar Super 300, FKM, Bolt coating

OUT A - NC, Flow adjustment

OUT B - NO, ON/OFF

◎ : 标准在庫品 (Standard stock)

○ : 受注生産品 (Made to order)

— : 无在庫 (Not stock)

① 阀门尺寸 (Valve size)		10		15		20		25	
	mm	Φ 10 × Φ 8		Φ 12 × Φ 10		Φ 19 × Φ 16		Φ 25 × Φ 22	
	inch	3/8" (× 1/4")		1/2" (× 3/8")		3/4" (× 5/8")		1" (× 7/8")	
② 连接方式 (Connection method)		mm	inch	mm	inch	mm	inch	mm	inch
F	Flowell 20series	○	○	○	○	○	○	○	○
FA	Flowell 20Aseries	○	○	○	○	○	○	○	○
R	Flowell 60series	○	○	○	○	○	○	○	○
H	Flowell 80series	○	○	○	○	○	○	○	○
P	Pillar Super fitting	○	○	○	○	○	○	○	○
S	Pillar Super 300	○	○	○	○	○	○	○	○
L	Pillar Super flare	○	○	○	○	○	○	○	○
K	Kurabo Final lock	○	○	○	○	○	○	○	○
C	Kurabo K-Fitter	○	○	○	○	○	○	○	○
B	Bueno Fit-One	○	○	○	○	○	○	○	○
X	Flare Type	—	○	—	○	—	○	—	○
T	Tube Type	○	○	○	○	○	○	○	○

③ 管道规格 (Tube Standard)

A	mm
B	inch

④ OUT A 制动方式 (Operation method)

2	NC (Normal Close)
9	NO (Normal Open)

⑥ OUT A 附加功能 (Additional function)

0	ON/OFF
1	流量调整功能 (Flow adjustment)

⑤ OUT B 制动方式 (Operation method)

2	NC (Normal Close)
9	NO (Normal Open)


⑦ OUT B 附加功能 (Additional function)

0	ON/OFF
1	流量调整功能 (Flow adjustment)

⑧ O-Ring ※1	
(No sign)	FKM
V	DAI-EL G902
E	EPDM

⑨ 螺母涂层 (Bolt coating) ※1	
(No sign)	无涂层(Not coated)
Y	有涂层 (Coated)

内部构造 (Internal structure)



品号 (No)	零件名 (Parts name)	材质 (Material)
①	外壳 (Case)	PP
②	活塞 (Piston)	PP
③	填料式旋塞阀 (Stuffing)	PP
④	薄膜 (Diaphragm)	PTFE
⑤	本体 (Body)	PTFE

Manifold

Tube Fitting

3-Way

Tube Fitting

规格 (Specifications)

使用流体 (Fluid)	化学品・纯水・气体 (Chemical liquid, DIW, Gas) ※2		
流体温度 (Fluid temperature range)	10～100℃		
大气温度 (Atmospheric temperature)	0～40℃		
液体流动部分的材质 (Materials of liquid flowed parts)	本体 (Body)	: PTFE	
	薄膜 (Diaphragm)	: PTFE	
操作方式 (Operating system)	单动式 (Spring return actuation)		
操作压力 (Pneumatic supply pressure)	0.3～0.6MPa		


阀门尺寸 (Valve size)		10 (3/8")	15 (1/2")	20 (3/4")	25 (1")
流通孔 (Orifice)		Φ8	Φ10	Φ16	Φ22
流体压力 (Fluid pressure range)					
0.3MPa规格 (0.3MPa specification)	IN→OUT	0～0.3MPa			
	背压 (Back pressure)	0～0.3MPa	0～0.2MPa	0～0.1MPa	

注释 (Note)
※1: 虽不接触流体, 但有腐蚀性高的流体时请选择。
※2: 气体在最大1cm³/min的时候, 有可能会发生阀底座泄露。

尺寸 (Dimensions)

- ▶ $\Phi 10 \times \Phi 8$
- ▶ $3/8" (\times 1/4")$

SAP3D - 10 - □□ - □□ - □□ - □ - □





连接方式 (Connection method)	A
Flowell 20series	77
Flowell 20Aseries	77
Flowell 60series	113
Flowell 80series	86
Pillar Super fitting	88
Pillar Super 300	85
Pillar Super flare	84.6
Kurabo Final lock	93
Kurabo K-Fitter	75
Bueno Fit-One	90.4
Flare Type	98.6
Tube Type	83

尺寸 (Dimensions)

- ▶ $\Phi 12 \times \Phi 10$
- ▶ $1/2" (\times 3/8")$

SAP3D - **15** - □□ - □□ - □□ - □ - □



连接方式 (Connection method)	A
Flowell 20series	85
Flowell 20Aseries	85
Flowell 60series	113
Flowell 80series	93
Pillar Super fitting	95
Pillar Super 300	93
Pillar Super flare	92.6
Kurabo Final lock	95
Kurabo K-Fitter	81
Bueno Fit-One	99
Flare Type	102.6
Tube Type	85

Manifold

Tube Fitting


3-Way

Tube Fitting

尺寸 (Dimensions)

- ▶ $\Phi 19 \times \Phi 16$
- ▶ $3/4" (\times 5/8")$

SAP3D - 20 - □□ - □□ - □□ - □ - □




连接方式 (Connection method)	A
Flowell 20series	107
Flowell 20Aseries	107
Flowell 60series	133
Flowell 80series	118
Pillar Super fitting	124
Pillar Super 300	117
Pillar Super flare	116.6
Kurabo Final lock	114
Kurabo K-Fitter	99
Bueno Fit-One	127
Flare Type	118.6
Tube Type	105

尺寸 (Dimensions)

- ▶ $\Phi 25 \times \Phi 22$
- ▶ 1" (× 7/8")

SAP3D - **25** - □□ - □□ - □□ - □ - □



Manifold

Tube Fitting

3-Way

Tube Fitting

连接方式 (Connection method)	A
Flowell 20series	144
Flowell 20Aseries	144
Flowell 60series	162
Flowell 80series	138
Pillar Super fitting	150
Pillar Super 300	146
Pillar Super flare	143
Kurabo Final lock	139
Kurabo K-Fitter	122
Bueno Fit-One	156
Flare Type	150
Tube Type	140